

## CLAIMS

1. A probe for use in a scanning probe microscope, comprising a single conductive material having a sharp end.

2. The probe as set forth in claim 1, wherein said single conductive material comprises one of W, Pt/Ir, Ni, Au and Ag.

3. A probe for use in a scanning probe microscope, comprising a single conductive wire having a sharp end.

4. The probe as set forth in claim 3, wherein said single conductive wire comprises one of W, Pt/Ir, Ni, Au and Ag.

5. A scanning probe microscope for a sample, comprising:

a probe having a body and a sharp end, said body and said sharp end including a single conductive material; and

a vibrating unit, provided at said body, for vibrating said sharp end along a direction approximately in parallel with a surface of said sample.

6. The scanning probe microscope as set forth in claim 5, wherein said single conductive material comprises one of W, Pt/Ir, Ni, Au and Ag.

7. The scanning probe microscope as set forth in claim 5, wherein said single conductive material comprises a wire.

8. The scanning probe microscope as set forth in claim 5, wherein said vibrating unit comprises a piezoelectric element.

9. The scanning probe microscope as set forth in claim 8, wherein said probe is electrically-isolated from said piezoelectric element.

10. The scanning probe microscope as set forth in claim 5, wherein said probe is vibrated at a resonance

frequency of said probe.

11. The scanning probe microscope as set forth in claim 8, wherein said probe is vibrated at a resonance frequency of said piezoelectric element.

5 12. The scanning probe microscope as set forth in claim 8, further comprising a detector, provided in a part of said piezoelectric element, for detecting a vibration state of said probe.

10 13. The scanning probe microscope as set forth in claim 12, further comprising a feedback control unit, connected to said detector, for performing a feedback control operation upon a distance between said the sharp end of said probe and said sample in accordance with the detected vibration state of said detector, so that the detected vibration state is brought close to a predetermined definite value.

14. A scanning probe microscope for a sample, comprising:

a probe having a conductive sharp end;

20 a moving unit for moving said sample along a Z-direction and moving said sample in X-and Y-directions;

25 a vibrating unit for vibrating said probe along a direction approximately in parallel with a surface of said sample;

a vibration detecting unit for detecting a vibration state of said probe;

30 a signal detecting unit for detecting an electrical characteristic signal between said probe and said sample;

a control unit for controlling an interaction between said probe and said sample so that the interaction is brought close to a predetermined definite level; and

35 a voltage applying unit for applying an AC/DC voltage to said sample.

Sub  
A16

15. The scanning probe microscope as set forth in claim 14, wherein said control unit comprises a feedback control unit for adjusting a distance between the sharp and of said probe and said sample so that the detected vibration state of said probe is brought close to a predetermined definite level.

16. The scanning probe microscope as set forth in claim 14, wherein the detected vibration state of said probe is one of a resonance amplitude and a resonance frequency of said probe.

17. The scanning probe microscope as set forth in claim 14, wherein the detected vibration state of said probe is one of a resonance amplitude and a resonance frequency of said vibrating unit.

18. The scanning probe microscope as set forth in claim 14, wherein the detected vibration state of said probe is a signal relating to a Q-value of vibration of said probe.

19. The scanning probe microscope as set forth in claim 14, wherein said control unit comprises a feedback control unit for adjusting a distance between the sharp and of said probe and said sample so that the detected electrical characteristic signal is brought close to a predetermined definite level.

20. The scanning probe microscope as set forth in claim 14, wherein said signal detecting unit comprises;  
a detector for detecting a signal from said probe;

a diode detector, connected to said detector, for detecting an output signal of said detector; and

a frequency detector, connected to said diode detector, for detecting an output signal of said diode detector by using a frequency close to a vibration frequency of said probe as a reference.

21. The scanning probe microscope as set forth in

35

Sub  
A17

claim 14, wherein said signal detecting unit comprises;  
a detector for detecting a signal from said probe;

a diode detector, connected to said detector, for detecting an output signal of said detector; and  
a frequency detector, connected to said diode detector, for detecting an output signal of said diode detector by using a frequency close to a frequency of said AC/DC voltage as a reference.

22. The scanning probe microscope as set forth in claim 14, wherein said signal detecting unit comprises;  
a detector for detecting a signal from said probe;

a diode detector, connected to said detector, for detecting an output signal of said detector;  
a first frequency detector, connected to said diode detector, for detecting an output signal of said diode detector by using a frequency close to a frequency of said AC/DC voltage as a reference; and

a second frequency detector, connected to said diode detector, for detecting an output signal of said diode detector by using a frequency close to a frequency of said AC/DC voltage as a reference.

23. The scanning probe microscope as set forth in claim 14, wherein said electrical characteristic signal shows a capacitance between said probe and said sample.

24. The scanning probe microscope as set forth in claim 14, wherein said electrical characteristic signal shows a differential component of a capacitance between said probe and said sample with respect to an AC component of said AC/DC voltage.

25. The scanning probe microscope as set forth in claim 14, wherein said electrical characteristic signal shows a differential component of a capacitance between said probe and said sample with respect to a vibration

coordinate of said probe.

Sub A19 5 26. The scanning probe microscope as set forth in claim 14, wherein said electrical characteristic signal shows a second-order differential component of a capacitance between said probe and said sample with respect to an AC component of said AC/DC voltage and a vibration coordinate of said probe.

10 27. The scanning probe microscope as set forth in claim 14, wherein said electrical characteristic signal shows a current flowing through said probe and said sample.

Sub A20 15 28. The scanning probe microscope as set forth in claim 14, wherein said electrical characteristic signal shows a differential component of a current flowing through said probe and said sample with respect to an AC component of said AC/DC voltage.

20 29. The scanning probe microscope as set forth in claim 14, wherein said electrical characteristic signal shows a differential component of a current flowing through said probe and said sample with respect to a vibration coordinate of said probe.

Sub A21 25 end 30. The scanning probe microscope as set forth in claim 14, wherein said electrical characteristic signal shows a second-order differential component of a current flowing through said probe and said sample with respect to an AC component of said AC/DC voltage and a vibration coordinate of said probe.

30 31. The scanning probe microscope as set forth in claim 14, wherein said electrical characteristic signal is detected under a condition that said probe and said sample are incorporated into a vacuum chamber.

35 32. The scanning probe microscope as set forth in claim 14, wherein said electrical characteristic signal is detected under a condition that a temperature of said probe and said sample is being changed.

33. The scanning probe microscope as set forth in claim 15, further comprising a display unit for displaying a surface information of said sample in accordance with the adjusted distance.

5 34. The scanning probe microscope as set forth in claim 19, further comprising a display unit for displaying the detected electrical characteristic signal.

Sub  
A22  
10 35. The scanning probe microscope as set forth in claim 14, wherein a frequency of an AC component of said AC/DC voltage is higher than a frequency of the vibration state of said probe.

36. A scanning probe microscope for a sample, comprising:

- a conductive probe;
- a control unit for controlling a relative location of said probe to said sample;
- a voltage applying unit for applying a voltage between said probe and said sample;
- a capacitance detecting unit for detecting a capacitance information between said probe and said sample;
- a calculating unit for calculating a first differential component of said capacitance information with respect to said voltage;
- 25 a calculating unit for calculating a second differential component of said capacitance information with respect to a coordinate; and
- a calculating unit for calculating a ratio of said second differential component to said first differential component.

30 37. The scanning probe microscope as set forth in claim 36, further comprising a calculating unit for calculating an integration value of said ratio with respect to said coordinate.

35 38. The scanning probe scanning microscope as set

said microscope further comprising a vibrating unit for vibrating said conductive probe along said coordinate, so that the second differential component of said capacitance information is a component of said capacitance information changing at a vibration frequency of said conductive probe.

39. The scanning probe microscope as set forth in claim 36, further comprising a calculating unit for converting said ratio into information regarding a concentration of majority carriers in equilibrium of said sample.

40. The scanning probe microscope as set forth in claim 39, further comprising a display unit for displaying said majority carrier concentration information.

41. The scanning probe scanning microscope as set forth in claim 36, further comprising a calculating unit for converting said ratio into information regarding a concentration of ionized dopants of said sample.

42. The scanning probe microscope as set forth in claim 41, further comprising a display unit for displaying said ionized dopant concentration information.

43. A method for controlling a scanning probe microscope for a sample, comprising: a probe having a conductive sharp end; a moving unit for moving said sample along a Z-direction and moving said sample in X- and Y-directions; a vibrating unit for vibrating said probe along a direction approximately in parallel with a surface of said sample; a vibration detecting unit for detecting a vibration state of said probe; a signal detecting unit for detecting an electrical characteristic signal between said probe and said sample; a control unit for controlling an interaction between said probe and said sample so that the interaction is brought close to a predetermined definite

Sub  
A27  
end

level; and a voltage applying unit for applying an AC/DC voltage to said sample,

5 said method comprising a step of adjusting a distance between the sharp end of said probe and said sample so that the detected vibration state of said probe is brought close to a predetermined definite level.

Sub  
A27

10 44. A method for controlling a scanning probe microscope for a sample, comprising: a probe having a conductive sharp end; a moving unit for moving said sample along a Z-direction and moving said sample in X- and Y-directions; a vibrating unit for vibrating said probe along a direction approximately in parallel with a surface of said sample; a vibration detecting unit for detecting a vibration state of said probe; a signal detecting unit for detecting an electrical characteristic signal between said probe and said sample; a control unit for controlling an interaction between said probe and said sample so that the interaction is brought close to a predetermined definite level; and a voltage applying unit for applying an AC/DC voltage to said sample,

15 said method comprising a step of adjusting a distance between the sharp end of said probe and said sample so that the detected electrical characteristic signal is brought close to a predetermined definite level.

25 45. The method as set forth in claim 44, further comprising the steps of:

detecting a signal from said probe by a detector diode-detecting an output signal of said detector by a diode; and

30 detecting an output signal of said diode by using a frequency close to a vibration frequency of said probe as a reference.

46. The method as set forth in claim 44, further comprising the steps of:

35 detecting a signal from said probe by a

Sub  
A25



detector;

detecting an output signal of said detector by a diode; and

detecting an output signal of said diode by using a frequency close to a frequency of an AC component of said AC/DC voltage as a reference.

47. The method as set forth in claim 44, further comprising the steps of:

detecting a signal from said probe by a detector;

detecting an output signal of said detector by a diode; and

detecting an output signal of said diode by using a frequency close to a frequency of an AC component of said AC/DC voltage as a reference and by using a frequency close to a vibration frequency of said probe as a reference.

48. The method as set forth in claim 44, wherein said electrical characteristic signal is detected under a condition that said probe and said sample are incorporated into a vacuum chamber.

49. The method as set forth in claim 44, wherein said electrical characteristic signal is detected under a condition that a temperature of said probe and said sample is being changed.

50. The method as set forth in claim 43, wherein a frequency of the vibration state of said probe is lower than a frequency of an AC component of said AC/DC voltage.

51. The method as set forth in claim 44, wherein a frequency of the vibration state of said probe is lower than a frequency of an AC component of said AC/DC voltage.

52. A scanning probe microscope for a sample, comprising:

a moving unit for moving said sample in X-, Y- and Z-directions;

a conductive probe approximately perpendicular to a surface of said sample and having a sharp end capable of being in proximity to the surface of said sample;

5

an oscillator;

a vibrating unit, connected to said oscillator, for vibrating said conductive probe in the X-direction in accordance with a frequency of said oscillator;

10

a vibration detecting unit for detecting a vibration amplitude of said conductive probe to generate a vibration voltage; and

a feedback control unit, connected between said vibration detecting unit and said moving unit, for controlling a location of said sample in the Z-direction in accordance with the detected vibration amplitude of said vibration detecting unit, so that the vibration amplitude of said vibrating detecting unit is brought close to a predetermined definite value.

15

20

53. The scanning probe microscope as set forth in claim 52, wherein said vibration detecting unit comprises a first lock-in amplifier for detecting a vibration frequency of said conductive probe using the frequency of said oscillator to generate a difference in phase between the vibration frequency of said conductive probe and the frequency of said oscillator as the detected vibration amplitude,

25

said feedback control unit comprising a servo circuit, connected to said first lock-in amplifier, for controlling the location of said sample in the Z-direction so that said difference in phase is brought close to a predetermined definite value.

30

35

54. The scanning probe microscope as set forth in claim 52, further comprising a first display unit, for displaying the location of said sample in the Z-direction while a predetermined area of said sample in the X- and

Y-directions is scanned by said conductive probe using said moving unit.

55. The scanning probe microscope as set forth in claim 52, further comprising:

an AC/DC voltage modulation circuit, connected to said sample, for supplying an AC/DC modulation voltage to said sample; and

a sensor, connected to said conductive probe, for detecting an electrical characteristic signal showing a state of said sample immediately below the sharp end of said conductive probe.

56. The scanning probe microscope as set forth in claim 55, wherein said sensor comprises a capacitance sensor.

57. The scanning probe microscope as set forth in claim 56, further comprising a second display unit for displaying a capacitance signal of said capacitance sensor while a predetermined area of said sample in the X- and Y-directions is scanned by said conductive probe using said moving unit.

58. The scanning probe microscope as set forth in claim 56, further comprising a second lock-in amplifier, connected to said capacitance sensor, for detecting a differential component of a capacitance signal of said capacitance sensor with respect to said AC/DC modulation voltage using a frequency thereof as a reference.

59. The scanning probe microscope as set forth in claim 58, further comprising a third display unit for displaying the differential component of the capacitance signal of said capacitance sensor with respect to said AC/DC modulation voltage while a predetermined area of said sample in the X- and Y-directions is scanned by said conductive probe using said moving unit.

60. The scanning probe microscope as set forth in claim 56, further comprising a third lock-in amplifier,

Sub  
A27  
encl

Sub  
A28

connected to said capacitance sensor, for detecting a differential component of a capacitance signal of said capacitance sensor with respect to a vibration direction of said conductive probe using a frequency of said oscillator as a reference.

61. The scanning probe microscope as set forth in claim 60, further comprising a fourth display unit for displaying the differential component of the capacitance signal of said capacitance sensor with respect to the vibration direction of said conductive probe while a predetermined area of said sample in the X- and Y- directions is scanned by said conductive probe using said moving unit.

62. The scanning probe microscope as set forth in claim 60, further comprising a fourth lock-in amplifier, connected to said third lock-in amplifier, for detecting a second-order differential component of the capacitance signal of said capacitance sensor with respect to the vibration direction of said conductive probe and said AC/DC voltage by said AC/DC modulation voltage using a frequency thereof as a reference.

63. The scanning probe microscope as set forth in claim 62, further comprising a fifth display unit for displaying the second-order differential component of the capacitance signal of said capacitance sensor while a predetermined area of said sample in the X- and Y- directions is scanned by said conductive probe using said moving unit.

64. The scanning probe microscope as set forth in claim 56, further comprising:

a second lock-in amplifier, connected to said capacitance sensor, for detecting a first differential component of a capacitance signal of said capacitance sensor with respect to said AC/DC modulation voltage using a frequency thereof as a reference;

a sixth display unit for displaying said integration value while a predetermined area of said sample in the X-and Y-directions is scanned by said

0545  
0546  
0547  
0548  
0549  
0550  
0551  
0552  
0553  
0554  
0555  
0556  
0557  
0558  
0559  
0560  
0561  
0562  
0563  
0564  
0565  
0566  
0567  
0568  
0569  
0570  
0571  
0572  
0573  
0574  
0575  
0576  
0577  
0578  
0579  
0580  
0581  
0582  
0583  
0584  
0585  
0586  
0587  
0588  
0589  
0590  
0591  
0592  
0593  
0594  
0595  
0596  
0597  
0598  
0599  
0600  
0601  
0602  
0603  
0604  
0605  
0606  
0607  
0608  
0609  
0610  
0611  
0612  
0613  
0614  
0615  
0616  
0617  
0618  
0619  
0620  
0621  
0622  
0623  
0624  
0625  
0626  
0627  
0628  
0629  
0630  
0631  
0632  
0633  
0634  
0635  
0636  
0637  
0638  
0639  
0640  
0641  
0642  
0643  
0644  
0645  
0646  
0647  
0648  
0649  
0650  
0651  
0652  
0653  
0654  
0655  
0656  
0657  
0658  
0659  
0660  
0661  
0662  
0663  
0664  
0665  
0666  
0667  
0668  
0669  
0670  
0671  
0672  
0673  
0674  
0675  
0676  
0677  
0678  
0679  
0680  
0681  
0682  
0683  
0684  
0685  
0686  
0687  
0688  
0689  
0690  
0691  
0692  
0693  
0694  
0695  
0696  
0697  
0698  
0699  
0700  
0701  
0702  
0703  
0704  
0705  
0706  
0707  
0708  
0709  
0710  
0711  
0712  
0713  
0714  
0715  
0716  
0717  
0718  
0719  
0720  
0721  
0722  
0723  
0724  
0725  
0726  
0727  
0728  
0729  
0730  
0731  
0732  
0733  
0734  
0735  
0736  
0737  
0738  
0739  
0740  
0741  
0742  
0743  
0744  
0745  
0746  
0747  
0748  
0749  
0750  
0751  
0752  
0753  
0754  
0755  
0756  
0757  
0758  
0759  
0760  
0761  
0762  
0763  
0764  
0765  
0766  
0767  
0768  
0769  
0770  
0771  
0772  
0773  
0774  
0775  
0776  
0777  
0778  
0779  
0780  
0781  
0782  
0783  
0784  
0785  
0786  
0787  
0788  
0789  
0790  
0791  
0792  
0793  
0794  
0795  
0796  
0797  
0798  
0799  
0800  
0801  
0802  
0803  
0804  
0805  
0806  
0807  
0808  
0809  
0810  
0811  
0812  
0813  
0814  
0815  
0816  
0817  
0818  
0819  
0820  
0821  
0822  
0823  
0824  
0825  
0826  
0827  
0828  
0829  
0830  
0831  
0832  
0833  
0834  
0835  
0836  
0837  
0838  
0839  
0840  
0841  
0842  
0843  
0844  
0845  
0846  
0847  
0848  
0849  
0850  
0851  
0852  
0853  
0854  
0855  
0856  
0857  
0858  
0859  
0860  
0861  
0862  
0863  
0864  
0865  
0866  
0867  
0868  
0869  
0870  
0871  
0872  
0873  
0874  
0875  
0876  
0877  
0878  
0879  
0880  
0881  
0882  
0883  
0884  
0885  
0886  
0887  
0888  
0889  
0890  
0891  
0892  
0893  
0894  
0895  
0896  
0897  
0898  
0899  
0900  
0901  
0902  
0903  
0904  
0905  
0906  
0907  
0908  
0909  
0910  
0911  
0912  
0913  
0914  
0915  
0916  
0917  
0918  
0919  
0920  
0921  
0922  
0923  
0924  
0925  
0926  
0927  
0928  
0929  
0930  
0931  
0932  
0933  
0934  
0935  
0936  
0937  
0938  
0939  
0940  
0941  
0942  
0943  
0944  
0945  
0946  
0947  
0948  
0949  
0950  
0951  
0952  
0953  
0954  
0955  
0956  
0957  
0958  
0959  
0960  
0961  
0962  
0963  
0964  
0965  
0966  
0967  
0968  
0969  
0970  
0971  
0972  
0973  
0974  
0975  
0976  
0977  
0978  
0979  
0980  
0981  
0982  
0983  
0984  
0985  
0986  
0987  
0988  
0989  
0990  
0991  
0992  
0993  
0994  
0995  
0996  
0997  
0998  
0999  
1000  
1001  
1002  
1003  
1004  
1005  
1006  
1007  
1008  
1009  
1010  
1011  
1012  
1013  
1014  
1015  
1016  
1017  
1018  
1019  
1020  
1021  
1022  
1023  
1024  
1025  
1026  
1027  
1028  
1029  
1030  
1031  
1032  
1033  
1034  
1035  
1036  
1037  
1038  
1039  
1040  
1041  
1042  
1043  
1044  
1045  
1046  
1047  
1048  
1049  
1050  
1051  
1052  
1053  
1054  
1055  
1056  
1057  
1058  
1059  
1060  
1061  
1062  
1063  
1064  
1065  
1066  
1067  
1068  
1069  
1070  
1071  
1072  
1073  
1074  
1075  
1076  
1077  
1078  
1079  
1080  
1081  
1082  
1083  
1084  
1085  
1086  
1087  
1088  
1089  
1090  
1091  
1092  
1093  
1094  
1095  
1096  
1097  
1098  
1099  
1100  
1101  
1102  
1103  
1104  
1105  
1106  
1107  
1108  
1109  
1110  
1111  
1112  
1113  
1114  
1115  
1116  
1117  
1118  
1119  
1120  
1121  
1122  
1123  
1124  
1125  
1126  
1127  
1128  
1129  
1130  
1131  
1132  
1133  
1134  
1135  
1136  
1137  
1138  
1139  
1140  
1141  
1142  
1143  
1144  
1145  
1146  
1147  
1148  
1149  
1150  
1151  
1152  
1153  
1154  
1155  
1156  
1157  
1158  
1159  
1160  
1161  
1162  
1163  
1164  
1165  
1166  
1167  
1168  
1169  
1170  
1171  
1172  
1173  
1174  
1175  
1176  
1177  
1178  
1179  
1180  
1181  
1182  
1183  
1184  
1185  
1186  
1187  
1188  
1189  
1190  
1191  
1192  
1193  
1194  
1195  
1196  
1197  
1198  
1199  
1200  
1201  
1202  
1203  
1204  
1205  
1206  
1207  
1208  
1209  
1210  
1211  
1212  
1213  
1214  
1215  
1216  
1217  
1218  
1219  
1220  
1221  
1222  
1223  
1224  
1225  
1226  
12

35

Sub  
A30  
end

conductive probe using said moving unit.

66. The scanning probe microscope as set forth in claim 55, wherein said sensor comprises a current sensor.

67. The scanning probe microscope as set forth in claim 66, further comprising a sixth display unit for displaying a current signal of said current sensor while a predetermined area of said sample in the X- and Y-directions is scanned by said conductive probe using said moving unit.

Sub  
A31

68. The scanning probe microscope as set forth in claim 66, further comprising a fifth lock-in amplifier, connected to said current sensor, for detecting a differential component of a current signal of said current sensor with respect to a voltage of said AC/DC modulation voltage using a frequency thereof as a reference.

69. The scanning probe microscope as set forth in claim 68, further comprising an eighth display unit for displaying the differential component of the current signal of said current sensor with respect to said AC/DC modulation voltage while a predetermined area of said sample in the X- and Y-directions is scanned by said conductive probe using said moving unit.

70. The scanning probe microscope as set forth in claim 66, further comprising a sixth lock-in amplifier, connected to said current sensor, for detecting a differential component of a current signal of said current sensor with respect to a vibration direction of said conductive probe using a frequency of said oscillator as a reference.

71. The scanning probe microscope as set forth in claim 70, further comprising a ninth display unit for displaying the differential component of the current signal of said current sensor with respect to the vibration direction of said conductive probe while a predetermined area of said sample in the X- and Y-directions is scanned

by said conductive probe using said moving unit.

Sub  
A32  
5 72. The scanning probe microscope as set forth in claim 70, further comprising a seventh lock-in amplifier, connected to said sixth lock-in amplifier, for detecting a second-order differential component of the current signal of said current sensor with respect to the vibration direction of said conductive probe and said AC/DC voltage by a frequency of said oscillator as a reference and said AC/DC modulation voltage using a frequency thereof as a  
10 reference.

15 73. The scanning probe microscope as set forth in claim 72, further comprising a tenth display unit for displaying the second-order differential component of the current signal of said current sensor while a predetermined area of said sample in the X- and Y- directions is scanned by said conductive probe using said moving unit.

20 74. The scanning probe microscope as set forth in claim 55, wherein a frequency of said AC/DC modulation voltage is higher than a frequency of the vibrating unit.

Sub  
A33  
25 75. The scanning probe microscope as set forth in claim 64, wherein said ratio shows information regarding a slope of a concentration of majority carriers in equilibrium with respect to said vibration direction when said AC/DC modulation voltage is small so as not to generate an inversion region in said sample.

30 76. The scanning probe microscope as set forth in claim 64, wherein said ratio shows information regarding a slope of a concentration of ionized dopants with respect to said vibration direction when said AC/DC modulation voltage is large so as to generate an inversion region in said sample.

35 77. The scanning probe microscope as set forth in claim 65, wherein said integration value shows information regarding a logarithmic value of a

Sub  
A33  
end  
5  
concentration of majority carriers in equilibrium with respect to said vibration direction when said voltage is small so as not to generate an inversion region in said sample.

78. The scanning probe microscope as set forth in claim 65, wherein said integration shows information regarding a logarithmic value of a concentration of ionized dopants with respect to said vibration direction when said voltage is large so as to generate an inversion region in said sample.

10

00001300-104304